

GHXV.EX28056 - Proportioners, Foam Concentrate

Proportioners, Foam Concentrate

Fierre Srl

VIA VIGENTINA 110/B
PAVIA, PV 27100 Italy

EX28056

BLADDER TANK AND RATIO-FLOW CONTROLLER INVESTIGATED TO UL 162

25 to 4000 gal capacity ASME for vertical installation and 50 to 4000 gal capacity ASME for horizontal installation.

Models FI-PM-X-UL-C and FI-PM-X-UL-S ratio flow controllers in sizes 2, 2-1/2, 3, 4 and 6 in.

Following are equivalent length valves for the controllers (Models FI-PM-X-UL-C and FI-PM-X-UL-S) based on a roughness factor of 130 and schedule 40 steel pipes.

Controller Size In.	Equivalent Length Ft
2	276
2-1/2	60
3	43
4	38
6	86

Refer to the individual foam concentrate Listings for operating limitations with specific combinations of foam concentrates and proportioner.

Last Updated on 2021-04-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"